

Autotrax 65 I-x specifications:

Autotrax 65 I-x



- GPRS: Class 12 Quad band GPRS.
- Supports Dual Profile Embedded and Normal SIM
- Provision for SMS fallback
- IRNSS GPS: L5 band 12 GNSS channels, 99 Acquisition channels, 33 Tracking Channels, Acquisition sensitivity -145dbm, Tracking sensitivity -160dbm, 2.5 meters CEP accuracy and inbuilt patch antenna.
 - o Hot start: 4Sec
 - o Warm start: 15 Sec
 - o Cold Start: 16 Sec
- Input output ports
 - o 4 digital inputs (2 Active High 2 Active Low)
 - o 2 Open collector Outputs
 - o 2 Analogue Inputs
 - o 2 RS232
 - o 1 USB configurable
- 3 Axis Accelerometer and Gyro sensor
- Internal storage of 40,000 way points
- Internal battery of for 4Hrs back up
- LED indications for unit health status
- Over The Air programmable Device
- Provision to connect with 3 URLs
- Panic key with blinking LED indication as well as LED for panic pressed indication. Structured such so that it can be cascaded with multiple panic as per requirements. Key also with protection to avoid accidental pressing.
- Operating temperature range -10 to + 70 Degree Celsius
- Provision to connect additional sensors such as Finger Print scanner, Card readers, Beacons, Fuel sensor, Temperature sensors, Voice box etc. Provision to connect OBD port.
- Distance and Geo fence based logics.
- IP 65 Ruggedised environmental proof design.
- Size 120mm x 68mm x 34mm, Weight: 206 grams.

**AIS 140
CERTIFIED**

**Time Tested, Long
life, Scalable Product**

**Ideal for normal
tracking as well as
complex fleet
management utility**

Arya Omnitalk Wireless Solutions Private Limited

CIN No.:U31100GJ1995PTC024599

Head Off. Unit No.A-202, 2nd Floor, Summer Court, Magarpatta City, Pune -411013 India

Tel : 9020-67470100 Fax : 91020 67470199

www.aryaomnitalk.com

